

Speed Queen

HORIZON LINE

SWF FRONTLOAD WASHER
SFE ELECTRIC DRYER
SFG GAS DRYER
ST STACK WASHER AND DRYER



Speed Queen

ULTRA HIGH EFFICIENCY WASHERS & DRYERS

Specifications - HORIZON WASHER, DRYER, STACKED UNIT

WASHER

	SWF
Width	683mm (26 7/8")
Depth	683mm (26 7/8")
Height	1107mm (43.6")
Water temperatures	Hot, warm and cold
Cycles	Normal, permanent press or delicate
Cycle time	Factory pre-set at 27.75 minutes, plus (heat) fill and drain
Basket volume	2.8 cu.ft. (79 litres)
Water pressure	Pressure fill - 20 to 120 psi (1.4/8.3 Bar)
Spin speed	Variable up to 1000rpm (max 300G)
Activation	Coin or manual operation*
Motor HP (Thermal protected)	Multi-speed, 3/4 HP
Top finish	Porcelain
Colour	White
Electrical specifications and circuit requirements	230v lph 50Hz (Boiler fed) or 415v 3ph 50hz (Electric heat) (3 phase not available on stack washer)
Net weight	127Kg (280lbs)
Shipping weight	132Kg (290lbs)

STACK WASHER AND DRYER

	ST
Width	683mm (26 7/8")
Depth	711mm (28")
Height	1943mm (76.5")
Net weight	Gas - 170Kg (375lbs) Electric - 168Kg (370lbs)
Shipping weight	Gas - 177Kg (390lbs) Electric - 174Kg (385lbs)

Refer to the separate washer and dryer charts for all other specifications of stacked unit.

DRYER

Electric Gas	SFE SFG
Width	683mm (26 7/8")
Depth	711mm (28")
Height	1107mm (43.6")
Cylinder volume	7.0 cu.ft. (201 litres)
Motor HP	1/3 HP, 5.5 amps
Heating element**	5350 watts, 240 volt
Btu per hour***	25,000 (6,300 kcal)
Type of gas (Gas models only)	Factory-equipped natural/ mixed gas. Convertible to LP gas.†
Utility connections	9.5mm (3/8" NPT)
Air outlet diameter	102mm (4")
Exhaust air flow****	220 CFM (105 litres/sec.)
Maximum exhaust static back pressure	0.6" W.G.
Activation	Coin or manual operation*
Top finish	Porcelain
Electrical specifications and circuit requirements	230v lph 50Hz, 13 amp (Gas) or 230v lph 50hz, 30 amp (Electric)
Colours	White
Net weight	Gas - 66Kg (145lbs) Electric - 64Kg (140lbs)
Shipping weight	Gas - 68Kg (150lbs) Electric - 66Kg (145lbs)

*Also Euro/token compatible

Electric model *Gas model ****Measured at point of exit from dryer.

† IMPORTANT: Any product revisions or conversions must be made by the Manufacturer's Authorised Dealers, Distributors, or local service personnel.

Distributed by:

 **Speed Queen**
Alliance Laundry Systems

